

## Endura® XL Miami-Dade FOG Control

### Miami-Dade DERM FOG Ordinance 2.0 Solutions

Each Endura® Miami-Dade DERM FOG ordinance approved solution is listed to 99% efficiency as per ASME A112.14.3. This product allows designers greater flexibility in accommodating Miami-Dade's jurisdictional requirements.

Endura® Grease Management products have been instrumental in changing the traditional practices regarding the design of grease management solutions. Thermoplastic hydromechanical alternatives to metal and concrete interceptors are being increasingly accepted Nationwide as the new standard for grease management in commercial foodservice applications.

#### Benefits:

- 99% efficiency FOG removal
- High capacity hydromechanical GI solutions
- Engineered thermoplastic
- Lightweight and easy to install
- Comes Standard with 'S' Rated Traffic Covers

#### Standards:



ASME A112.14.3

Endura XL	Part Number	Product Code
Endura XL 50 GPM w/ S-Rated Traffic Cover (w/external flow control)	4050HEA04	766132
Endura XL 75 GPM w/ S-Rated Traffic Cover (w/ external flow control)	4075HEA04	766131



#### Contact us

Visit our website: [ipexna.com/](http://ipexna.com/)  
[enduragreasemanagement.com](http://enduragreasemanagement.com)

Eastern U.S. Toll free: (800) 463-9572  
Western U.S. Toll free: (888) 461-5307

Endura® is a registered trademark.

## Miami-Dade DERM FOG Ordinance 2.0 Solutions at 99% Efficiency

Product (w/ external flow control)	Part Number	Product Code	Approved Configuration	GPM	1 GL	2 GL	3 GL	4 GL
					Capacity (lbs)			
 *	3935A04	763541	2 units in series	35	0	214.76	214.76	429.52
	4050HEA04	766132	1 unit	50	108.87	217.74	326.61	435.48
	4075HEA04	766131	1 unit	75	192.98	385.96	578.94	771.92
 *	4075A04	766014	2 units in series	75	0	1098.76	1098.76	2197.52
 *	40100A04	766012	2 units in series	100	0	1486.97	1486.97	2973.94

\* Requires minimum of 2 units in series to meet requirement of Miami-Dade DERM FOG Ordinance 2.0