



# POWER & COMMUNICATION DUCT

## TYPE EB-35 & TYPE DB-120

### PRODUCT INFORMATION BULLETIN

#### SPECIFICATION:

- ASTM D 1784  
"PVC Plastic Compounds"
- NEMA TC-8  
"Plastic Utilities Duct for Underground Installation"
- ASTM F 512  
"Smooth-Wall Poly Vinyl-Chloride (PVC) Conduit and Fittings for Underground Installation"

**IPEX Pipe Type EB-35 & DB-120 Ducts are rated for 90°C cable.**

#### IPEX USA LLC

Toll Free: (800) 463-9572  
Fax: (905) 403-9195  
[www.ipexamerica.com](http://www.ipexamerica.com)

Products are manufactured by IPEX Electrical Inc. and distributed in the United States by IPEX USA LLC.

Super Duct™ is a trademark of IPEX Branding Inc.

#### Type EB-35 • Rated For 90°C Cable 20 Foot Length Belled One End

| Nominal Size (in) | Product Code | Average O.D. | Minimum Wall | Feet/Pallet | Approx. Wgt/100ft. |
|-------------------|--------------|--------------|--------------|-------------|--------------------|
| 2                 | 008921       | 2.375        | 0.060        | 2800        | 33                 |
| 3                 | 008931       | 3.500        | 0.076        | 2000        | 64                 |
| 4                 | 008941       | 4.500        | 0.100        | 1140        | 105                |
| 5                 | 008951       | 5.563        | 0.126        | 760         | 161                |
| 6                 | 008961       | 6.625        | 0.152        | 520         | 230                |

#### Type DB-120 • Rated For 90°C Cable 20 Foot Length Belled One End

| Nominal Size (in) | Product Code | Average O.D. | Minimum Wall | Feet/Pallet | Approx. Wgt/100ft. |
|-------------------|--------------|--------------|--------------|-------------|--------------------|
| 2                 | 008621       | 2.375        | 0.077        | 2800        | 42                 |
| 3                 | 008631       | 3.500        | 0.118        | 2000        | 96                 |
| 4                 | 008641       | 4.500        | 0.154        | 1140        | 158                |
| 5                 | 008651       | 5.563        | 0.191        | 760         | 240                |
| 6                 | 008661       | 6.625        | 0.227        | 520         | 336                |

