



IPEX USA LLC.

QUARTER TURN VALVE AUTOMATION SUBMITTAL

Job Information (please print clearly)

Customer		Contact Name	Date
City/State	Phone	E-mail	
Job Name		Job Location	
End-User	Engineer	Contractor	

Application Information (please print clearly)

Application Description

Type of Fluid	Flow Rate	Pressure	Temperature
	GPM	PSI	°F

Valve Information

Valve Operation: On/Off Flow Regulation

Valve Type

	Size	Body Material	Seals	End Connections
<input type="checkbox"/> Ball Valve		<input type="checkbox"/> PVC <input type="checkbox"/> PP <input type="checkbox"/> CPVC <input type="checkbox"/> PP-n <input type="checkbox"/> ABS <input type="checkbox"/> PVDF	<input type="checkbox"/> EPDM <input type="checkbox"/> FPM	<input type="checkbox"/> Socket (IPS) <input type="checkbox"/> Threaded (FNPT) <input type="checkbox"/> Flanged (ANSI 150)
<input type="checkbox"/> Butterfly Valve		<input type="checkbox"/> PP <input type="checkbox"/> ABS <input type="checkbox"/> PVC <input type="checkbox"/> PVDF <input type="checkbox"/> CPVC	<input type="checkbox"/> EPDM <input type="checkbox"/> FPM <input type="checkbox"/> NBR	<input type="checkbox"/> Wafer <input type="checkbox"/> SS Lugs (ANSI 150 Flanged)
<input type="checkbox"/> 3-Way Ball Valve		<input type="checkbox"/> PVC <input type="checkbox"/> CPVC <input type="checkbox"/> PP	<input type="checkbox"/> EPDM <input type="checkbox"/> FPM	<input type="checkbox"/> Socket (IPS) <input type="checkbox"/> Threaded (FNPT) <input type="checkbox"/> Flanged (ANSI 150)

Actuator Type

<input type="checkbox"/> Pneumatic	Air Supply Pressure		Type				
	<input type="checkbox"/> 80 psi <input type="checkbox"/> Other:		<input type="checkbox"/> Double Acting <input type="checkbox"/> Spring Return, Fail Close <input type="checkbox"/> Spring Return, Fail Open				
	Pilot Solenoid						
	Type <input type="checkbox"/> 3-Way <input type="checkbox"/> 4-Way		Voltage <input type="checkbox"/> 120V AC <input type="checkbox"/> 24V DC <input type="checkbox"/> Other:				
			Protection Rating <input type="checkbox"/> 4/4x <input type="checkbox"/> 7/9 <input type="checkbox"/> Other:				
	Limit Switches						
Type <input type="checkbox"/> SPDT-Mechanical <input type="checkbox"/> SPDT-Proximity <input type="checkbox"/> Other:		Protection Rating <input type="checkbox"/> 4/4x <input type="checkbox"/> 7/9 <input type="checkbox"/> Other:					
Positioner							
Input Signal <input type="checkbox"/> 3-15 psi <input type="checkbox"/> 4-20 mA <input type="checkbox"/> Other:		Options <input type="checkbox"/> Limit Switch (LS) <input type="checkbox"/> Position Transmitter (PT) <input type="checkbox"/> LS and PT <input type="checkbox"/> Intrinsically Safe					
Other Options							
<input type="checkbox"/> Declutchable Manual Override <input type="checkbox"/> Muffler – Brass/Bronze <input type="checkbox"/> Speed Control – Brass/Bronze <input type="checkbox"/> L-Port Actuator Beacon Kit <input type="checkbox"/> T-Port Actuator Beacon Kit							
<input type="checkbox"/> Electric	Voltage		Protection Rating		Rotation		
	<input type="checkbox"/> 100-240V AC <input type="checkbox"/> 24V AC/DC <input type="checkbox"/> 12V AC/DC <input type="checkbox"/> Other:		<input type="checkbox"/> 4/4x <input type="checkbox"/> 7/9 <input type="checkbox"/> Other:		<input type="checkbox"/> 90° (Standard) <input type="checkbox"/> 180° <input type="checkbox"/> 270° <input type="checkbox"/> Other:		
	Positioner					More Options	
	Input Signal <input type="checkbox"/> 4-20 mA <input type="checkbox"/> 0-10V DC <input type="checkbox"/> Other:					<input type="checkbox"/> Battery Backup <input type="checkbox"/> Other:	



Phone: 1-800-463-9572
 Fax: 905-844-0826
 URL: ipexamerica.com
 Email: automation@ipexamerica.com

SUBMIT